

PRO CARE II™

Portable Delivery Unit with Saliva Ejector Suction



DNTLworks™
Equipment Corporation

QUALITY CONSTRUCTION, INTEGRATED COMPONENTS,
AND LOW PRICE MAKE THE PRO CARE II™ ONE OF THE
BEST OVERALL VALUES AVAILABLE.

The ProCare II is ideal for missionary work, remote clinics, private home care, nursing homes, military, and many other basic applications.

As a basic portable dental delivery unit, the ProCare II features two handpiece connections, an air/water syringe and saliva ejector suction.

The quiet, internal compressor, separate suction pump (not a venturi), and 500 ml water/air reservoir eliminate dependence on local air and water sources. A contoured case with nylon shoulder strap makes the ProCare II unit convenient to carry.

All handpiece and suction tubing, as well as the hospital-grade power cord are safely stored inside the case during transport. The ProCare II fits easily inside a vehicle or cabinet.



**Complete
Portable
Lightweight
Compact**

DNTLworks™ Equipment Corp.
15504 East Hinsdale Circle, Unit B
Englewood, CO 80112 U.S.A.
(303) 693-1410
FAX (303) 693-6189
(800) 847-0694

FEATURES INCLUDE:

- ⊕ *Quiet, 1/3 HP oil-free compressor*
- ⊕ *Two-handpiece connections with manual selection for one highspeed and one lowspeed handpiece*
- ⊕ *Integrated water supply to highspeed handpiece*
- ⊕ *Coiled asepsis tubing accomodates most brands of handpieces*
- ⊕ *Separate, internal saliva ejector suction pump (not a venturi)*
- ⊕ *Non-retracting water relay*
- ⊕ *Air/Water syringe*
- ⊕ *Electric foot switch*
- ⊕ *Built-in instrument tray/storage bin*
- ⊕ *Lockable, lightweight, impact resistant case with handle and nylon carrying strap*
- ⊕ *Proudly 100% made in USA*

PRO CARE II™

Portable Delivery Unit with Saliva Ejector Suction



DNTLworks™
Equipment Corporation



SPECIFICATIONS

Case Size (L/W/D): 22.5" x 13.5" x 12.25"
(57.2 cm x 34.3 cm x 31.1 cm)

Case Type: Polypropylene

Weight: 35 lbs (15.9 kg)

Sound Level: 46 dB

Working Pressure: 25 psi

Horsepower: 1/3 hp

Air/water Reservoir: 500 ml

Power Supply: 115 vac or 220 vac

Current: 3.3 amps

Wattage: 380

Frequency: 60 Hz or 50 Hz

Compressor Type: Oil-free, diaphragm

Vacuum Type: Peristaltic pump

Waste Container: 1 Quart (946 ml)

DNTLworks™ Equipment Corp.
15504 East Hinsdale Circle, Unit B
Englewood, CO 80112 U.S.A.
(303) 693-1410
FAX (303) 693-6189
(800) 847-0694