

PROSEAL™

Portable Sealant Units



DNTLworks™
Equipment Corporation

THE EXCEPTIONALLY POWERFUL AND QUIET PROSEAL I™ AND PROSEAL II™ PORTABLE SEALANT UNITS FROM DNTLworks EQUIPMENT CORPORATION HAVE SET THE STANDARD FOR QUALITY IN SEALANT PROGRAMS.

The versatile, one-piece configuration of the ProSeal I includes a powerful, quiet vacuum pump, large waste container, and a compressor powering an air/water syringe and an integrated water source. Additionally, the ProSeal II features a multi-function handpiece for prophylaxis and other dental delivery applications.

The ProSeal units, weighing between 38 and 43 pounds, incorporate built-in wheels and a retractable handle for easy transportation.

The integrated features of the ProSeal I and ProSeal II make these easy-to-use units an outstanding foundation for any sealant program.



ProSeal I

FEATURES INCLUDE:

- ⊕ *Impact-resistant case incorporates built-in wheels and retractable handle*
- ⊕ *Powerful, quiet vacuum pump with dual hoses for HVE and saliva ejector use*
- ⊕ *Integrated, non-retracting water source with air/water syringe for irrigation and drying*
- ⊕ *Large waste container with automatic overflow shutoff*
- ⊕ *Multi-function, electric handpiece in ProSeal II*
- ⊕ *Hospital grade wiring with 15 amp circuit breaker*
- ⊕ *Made with pride in the USA*

ProSeal is a trademark of
DNTLworks Equipment Corporation © 1998



***Lightweight
Powerful
Quick Set-up
Easy to Use***

DNTLworks™ Equipment Corp.
15504 East Hinsdale Circle, Unit B
Englewood, CO 80112 U.S.A.
(303) 693-1410
FAX (303) 693-6189
(800) 847-0694

PROSEAL™

Portable Sealant Units



DNTLworks™
Equipment Corporation

SPECIFICATIONS

DIMENSIONS/WEIGHT

Length: 21.9" (55.6 cm)

Width: 8.4" (21.3 cm)

Height: 18" (45.7 cm)

Weight: ProSeal I - 38 lbs (17.3 kg)

ProSeal II - 43 lbs (19.5 kg)

VACUUM MOTOR

Power: 1/3 hp

Vacuum Strength: 0" to 21" Hg
(adjustable)

Vacuum Flow: 4.6 cfm

Waste Receptacle: 1200 ml

Sound Level: 46 dB

Automatic Overflow Shutoff Valve

ELECTRICAL

Power Supply: 115 vac or 220 vac

Frequency: 50 or 60 Hz

Circuit Breaker: 15 amps

Hospital Grade Wiring: NEMA Type
5-15P Plug

HANDPIECE - PROSEAL II ONLY

Speed: 0 - 40,000 rpm

Disposable Prophy Attachment Included

Latch-type Prophy Attachment Available



ProSeal II

FEATURES INCLUDE:

- ⊕ *Lightweight, one-piece design*
- ⊕ *Impact-resistant case with built-in wheels and retractable handle*
- ⊕ *Powerful vacuum pump with dual hose design accommodates many brands of HVE and saliva ejector tips*
- ⊕ *Non-retracting water source with air/water syringe*
- ⊕ *Electric handpiece in ProSeal II*
- ⊕ *Hospital grade wiring with 15 amp circuit breaker protection*
- ⊕ *Built-in carrying handle*
- ⊕ *Small size for convenient storage*
- ⊕ *Easy access through side door*
- ⊕ *Lightweight, yet rugged*

DNTLworks™ Equipment Corp.
15504 East Hinsdale Circle, Unit B
Englewood, CO 80112 U.S.A.
(303) 693-1410
FAX (303) 693-6189
(800) 847-0694